Model/s:			SRS 28				
Condensing Boiler/s:			Yes				
Low Temperature (**) Boiler/s:			No				
B11 Boiler/s:			No				
Cogeneration Space Heater:			No	Equipped with a supplementary heating system: No		No	
Combination Heater:			Yes				
ltem	Symbol	Value	Unit	Item	Symbol	Value	Unit
Nominal heat output	P _{rated}	28	kW	Seasonal space heating energy efficiency	ης	92,816	%
				Energy efficiency class		Α	
For boiler space heaters and boiler combination heaters: Useful heat output				For boiler space heaters and boiler combination heaters: Useful efficiency			
At nominal heat output and high- temperature regime (*)	P ₄	27,082	kW	At nominal heat output and high- temperature regime (*)	η ₄	87,095	%
At 30% of nominal heat output and low- temperature regime (**)	P ₁	2,727	kW	At 30% of nominal heat output and low- temperature regime (**)	η1	97,457	%
Auxiliary electricity consumption				Other items			
At full load	el _{max}	0,084	kW	Standby heat losses	P _{stby}	0,054	kW
At part load	el _{min}	0,037	kW	Ignition burner energy consumption	P _{ign}	3,593	kW
In standby mode	P _{SB}	0,003	kW	Sound power level, indoors	L _{WA}	40	dB
For boiler combination heaters:							
Declared load profile:	XL		1	Domestic hot water production efficiency		86,318	%
	ΛL			Energy efficiency class	η _{wн}	Α	70
Daily electrical power consumption	Q _{elec}	0,170	kWh	Daily gas consumption	Q _{fuel}	22,442	kWh
Annual electricity consumption	AEC	37,489	kWh	Annual fuel consumption	AFC	17,774	GJ
Contact information	ALARKO CARRIER SAN. TİC. A.Ş., GOSB - Gebze O.S.B., Şahabettin Bilgisu Cad., 41400, Gebze/Kocaeli/Turkey						
(*) High temperature regime means 60 °C	on return and	80 °C on flo	w.				
(**) Low temperature regime means 30 °C 1	or condensing	boilers, 37	°C for low-tempera	ature boilers and 50 °C for for other appliances on	return tempe	rature.	