

Model/s:				SSP 20				
Condensing Boiler/s:				Yes				
Low Temperature (**) Boiler/s:				No				
B11 Boiler/s:				No				
Cogeneration Space Heater:				No			Equipped with a supplementary heating system:	No
Combination Heater:				Yes				
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit	
Nominal heat output	P_{rated}	19,6	kW	Seasonal space heating energy efficiency	η_s	91,4	%	
				Energy efficiency class		A		
<i>For boiler space heaters and boiler combination heaters: Useful heat output</i>				<i>For boiler space heaters and boiler combination heaters: Useful efficiency</i>				
At nominal heat output and high-temperature regime (*)	P_4	19,6	kW	At nominal heat output and high-temperature regime (*)	η_4	88,0	%	
At 30% of nominal heat output and low-temperature regime (**)	P_1	6,1	kW	At 30% of nominal heat output and low-temperature regime (**)	η_1	97,3	%	
<i>Auxiliary electricity consumption</i>				<i>Other items</i>				
At full load	e_{lmax}	0,080	kW	Standby heat losses	P_{stby}	0,065	kW	
At part load	e_{lmin}	0,033	kW	Ignition burner energy consumption	P_{ign}	0,000	kW	
In standby mode	P_{SB}	0,004	kW	Annual energy consumption	Q_{HE}	36	GJ	
				Sound power level, indoors	L_{WA}	39	dB	
				Emissions of nitrogen oxides	NO_x	34,763	mg/kWh	
For boiler combination heaters:								
Declared load profile:	XL			Domestic hot water production efficiency	η_{WH}	91,3	%	
				Energy efficiency class		A		
Daily electrical power consumption	Q_{elec}	0,191	kWh	Daily gas consumption	Q_{fuel}	20,824	kWh	
Annual electricity consumption	AEC	41,958	kWh	Annual fuel consumption	AFC	16,493	GJ	
Contact information	ALARKO CARRIER SAN. TIC. A.Ş., GÖSB - Gebze O.S.B., Şahabettin Bilgisu Cad., 41400, Gebze/Kocaeli/Turkey							
(*) High temperature regime means 60 °C on return and 80 °C on flow.								
(**) Low temperature regime means 30 °C for condensing boilers, 37 °C for low-temperature boilers and 50 °C for for other appliances on return temperature.								