Model/s:			SRS 28					
Condensing Boiler/s:			Yes					
Low Temperature (**) Boiler/s: B11 Boiler/s: Cogeneration Space Heater: Combination Heater:			No					
			No					
			No	Equipped with a supplementary heating system:			No	
			Yes					
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit	
Nominal heat output	D.	28	kW	Seasonal space heating energy efficiency	ης	92,816	%	
	P _{rated}			Energy efficiency class		Α		
For boiler space heaters and boiler combination heaters: Useful heat output				For boiler space heaters and boiler combination heaters: Useful efficiency				
At nominal heat output and high- temperature regime (*)	P ₄	27,082	kW	At nominal heat output and high-temperature regime (*)	η_4	87,095	%	
At 30% of nominal heat output and low- temperature regime (**)	P ₁	2,727	kW	At 30% of nominal heat output and low- temperature regime (**)	η ₁	97,457	%	
Auxiliary electricity consumption	•		•	Other items		•	•	
At full load	el _{max}	0,084	kW	Standby heat losses	P _{stby}	0,054	kW	
At part load	el _{min}	0,037	kW	Ignition burner energy consumption	P _{ign}	3,593	kW	
In standby mode	P _{SB}	0,003	kW	Sound power level, indoors	L _{WA}	40	dB	
For boiler combination heaters:	•		•					
Declared load profile:		V	1	Domestic hot water production efficiency	_	86,318	- %	
	XL			Energy efficiency class	η _{wн}	Α	70	
Daily electrical power consumption	Q _{elec}	0,170	kWh	Daily gas consumption	Q _{fuel}	22,442	kWh	
Annual electricity consumption	AEC	37,489	kWh	Annual fuel consumption	AFC	17,774	GJ	
Contact information	ALARKO CARRIER SAN. TİC. A.Ş., GOSB - Gebze O.S.B., Şahabettin Bilgisu Cad., 41400, Gebze/Kocaeli/Turkey							

^(*) High temperature regime means 60 °C on return and 80 °C on flow.

^(**) Low temperature regime means 30 °C for condensing boilers, 37 °C for low-temperature boilers and 50 °C for for other appliances on return temperature.